

INDUSTRIAL COMPONENT DATA

P1-25/M4/K1-PR/N 172773 Y7-172773 EATON ELECTRIC Main switch, 3 pole + N, 25 A, Emergency-Stop function, Loc..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/M4/K1-PR/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/M4/K1-PR/N
Catalog number	Y7-172773
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7B42D171FA
Generated	2026-08-04

Product Overview

Main switch, 3 pole + N, 25 A, Emergency-Stop function, Lockable in the 0 (Off) position, rear mounting, with 400 mm metal shaft

P1-25/M4/K1-PR/N

Main switch, P1, 25 A, rear mounting, 3 pole + N, Emergency switching off function, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, P1, 25 A, rear mounting, 3 pole + N, Emergency switching off function, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mmMain switch, P1, Rated uninterrupted current (Iu): 25 A, Functions: Interlockable, Emergency switching off function, Fitted with: Metal shaft for a control panel depth of 400 mm, Red rotary handle and yellow locking ring, Mounting method: Rear mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

General specificationsProduct nameEaton Moeller® series P1 Main switchPart

no.P1-25/M4/K1-PR/NEAN4015081693917Product Length/Depth340 millimetreProduct height70 millimetreProduct width71 millimetreProduct weight0.335 kilogramCertificationsIEC/EN 60947-3

IEC/EN 60947

VDE 0660

IEC/EN 60204Product TradenameP1Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time

Withstand Current (Icw) for a time of 1 second
Features & Functions
Version as emergency stop installation
Version as maintenance-/service switch
Version as main switch
Fitted with: Metal shaft for a control panel depth of 400 mm
Red rotary handle and yellow locking ring
Functions
Interlockable
Emergency switching off function
Locking facility
Lockable in the 0 (Off) position
Number of poles 4
General information
Accessories
Auxiliary contact fitted by user.
Degree of protection NEMA 12
Degree of protection (front side) IP65
Lifespan, mechanical 300,000 Operations
Mounting method Rear mounti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/M4/K1-PR/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.