

INDUSTRIAL COMPONENT DATA

P1-25/V/SVB 055335 Y7-55335 EATON ELECTRIC Main switch, 3 pole, 25 A, Emergency-Stop function, Lockable in t..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/V/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/V/SVB
Catalog number	Y7-55335
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-551ECD9B
Generated	2026-08-05

Product Overview

Main switch, 3 pole, 25 A, Emergency-Stop function, Lockable in the 0 (Off) position, rear mounting

General Switch 3 poles 25 A Bottom mount panel Handle

Eaton Moeller® series P1 Main switch, P1, 25 A, rear mounting, 3 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 25 A, Functions: Interlockable, Emergency switching off function, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Rear mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 055335 Model Code P1-25/V/SVB EAN

4015080553359 Product Length/Depth 131 mm Product Height 65 mm Product Width 65 mm Product Weight 0.217 kg

Certifications CSA-C22.2 No. 94

CSA File No.: 012528

UL Category Control No.: NLRV

VDE 0660

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

UL 60947-4-1

CE

CSA Class No.: 3211-05

UL File No.: E36332

CSA

IEC/EN 60947-3

IEC/EN 60204

UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 055335 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

25 A

Rated permanent current at AC-23, 400 V (EF011777)

25 A

Rated permanent current at AC-21, 400 V (EF009165)

25 A

Rated operation power at AC-3, 400 V (EF001364)

7.5 kW

Rated short-time withstand current I_{cw} (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

13 kW

Switching power at 400 V (EF009166)

13 kW

Conditioned rated short-circuit current I_q (EF001444)

50 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/V/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.