

INDUSTRIAL COMPONENT DATA

P1-32/EA/SVB-SW/HI11 012772 Y7-12772 EATON ELECTRIC

Main switch, 3 pole + 1 N/O + 1 N/C, 32 A, STOP function..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/EA/SVB-SW/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/EA/SVB-SW/HI11
Catalog number	Y7-12772
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-34520BD48D
Generated	2026-08-04

Product Overview

Main switch, 3 pole + 1 N/O + 1 N/C, 32 A, STOP function, Lockable in the 0 (Off) position, flush mounting
General Switch 3 poles + 1 NO + 1 NC 32 A Flush mount
Eaton Moeller® series P1 Main switch, P1, 32 A, flush mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position
Main switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Mounting method: Flush mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications
Product Name Eaton Moeller® series P1 Main switch Catalog Number 012772 Model Code P1-32/EA/SVB-SW/HI11 EAN 4015080127727 Product Length/Depth 120 mm Product Height 70 mm Product Width 65 mm Product Weight 0.232 kg
Certifications CSA File No.: 012528
CSA-C22.2 No. 94
CSA
UL 60947-4-1
UL Category Control No.: NLRV
VDE 0660

CE

IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

UL

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 012772 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

13 kW

Rated short-time withstand current Icw (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current Iq (EF001444)

80 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/EA/SVB-SW/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.