

INDUSTRIAL COMPONENT DATA

**P1-32/V/SVB-SW/HI11 017518 Y7-17518 EATON ELECTRIC
Main switch, 3 pole + 1 N/O + 1 N/C, 32 A, STOP function,..**

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/V/SVB-SW/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/V/SVB-SW/HI11
Catalog number	Y7-17518
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-843E74FD81
Generated	2026-08-06

Product Overview

Main switch, 3 pole + 1 N/O + 1 N/C, 32 A, STOP function, Lockable in the 0 (Off) position, rear mounting

General Switch 3 poles + 1 NO + 1 NC 32 A Panel bottom mount

Eaton Moeller® series P1 Main switch, P1, 32 A, rear mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: Interlockable, STOP function, Fitted with: Black rotary handle and locking ring, Mounting method: Rear mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 017518 Model Code P1-32/V/SVB-SW/HI11 EAN 4015080175186 Product Length/Depth 90 mm Product Height 70 mm Product Width 63 mm Product Weight 0.257 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60947

UL 60947-4-1

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

CE
UL File No.: E36332
CSA Class No.: 3211-05
CSA
IEC/EN 60947-3
IEC/EN 60204
VDE 0660
UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 017518 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
32 A
Rated permanent current at AC-23, 400 V (EF011777)
32 A
Rated permanent current at AC-21, 400 V (EF009165)
32 A
Rated operation power at AC-3, 400 V (EF001364)
13 kW
Rated short-time withstand current I_{cw} (EF007050)
0.64 kA
Rated operation power at AC-23, 400 V (EF007027)
15 kW
Switching power at 400 V (EF009166)
15 kW
Conditioned rated short-circuit current I_q (EF001444)
80 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/V/SVB-SW/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.