

## INDUSTRIAL COMPONENT DATA

# P1-32/EA/SVB/2HI11 012540 Y7-12540 EATON ELECTRIC Main switch, 3 pole + 2 N/O + 2 N/C, 32 A, Emergency-Stop ..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/EA/SVB/2HI11



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P1-32/EA/SVB/2HI11  |
| Catalog number  | Y7-12540            |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-AC283FF030       |
| Generated       | 2026-08-05          |

## Product Overview

Main switch, 3 pole + 2 N/O + 2 N/C, 32 A, Emergency-Stop function, flush mounting

General Switch 3 poles + 2 NO + 2 NC 32 A Flush mount

Eaton Moeller® series P1 Main switch, P1, 32 A, flush mounting, 3 pole, 2 N/O, 2 N/C, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: Interlockable, Emergency switching off function, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Flush mounting, Number of poles: Three-pole, Degree of Protection: NEMA 1

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 012540 Model Code P1-32/EA/SVB/2HI11 EAN 4015080125402 Product Length/Depth 120 mm Product Height 70 mm Product Width 65 mm Product Weight 0.272 kg

Certifications IEC/EN 60947-3

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CSA

UL 60947-4-1

CE

CSA Class No.: 3211-05

CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60204

IEC/EN 60947

UL

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second  
ETIM for 012540 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U<sub>e</sub> AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I<sub>u</sub> (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

13 kW

Rated short-time withstand current I<sub>cw</sub> (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current I<sub>q</sub> (EF001444)

80 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed conta...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/EA/SVB/2HI11 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.