

## INDUSTRIAL COMPONENT DATA

**P3-63/EA/SVB-SW/2HI11 012653 Y7-12653 EATON ELECTRIC  
Main switch, 3 pole + 2 N/O + 2 N/C, 63 A, STOP functio..**

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/EA/SVB-SW/2HI11



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | EATON - MOELLER       |
| MPN / Reference | P3-63/EA/SVB-SW/2HI11 |
| Catalog number  | Y7-12653              |
| Category        | Switch disconnecter   |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-25CF79B4DE         |
| Generated       | 2026-08-05            |

**Product Overview**

Main switch, 3 pole + 2 N/O + 2 N/C, 63 A, STOP function, flush mounting

General Switch 3 poles + 2 NO + 2 NC 63 A Flush mount

Eaton Moeller® series P3 Main switch, P3, 63 A, flush mounting, 3 pole, 2 N/O, 2 N/C, STOP function, With black rotary handle and locking ring

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I<sub>u</sub> = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, NEMA12

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series P3 Main switch Catalog Number 012653 Model Code P3-63/EA/SVB-SW/2HI11 EAN 4015080126539 Product Length/Depth 128 mm Product Height 102 mm Product Width 114 mm Product Weight 0.506 kg

Certifications IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA-C22.2 No. 94

CSA File No.: 012528

UL File No.: E36332

IEC/EN 60204

CSA

CE

UL 60947-4-1

UL Category Control No.: NLRV

VDE 0660

CSA Class No.: 3211-05

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 012653 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

63 A

Rated permanent current at AC-23, 400 V (EF011777)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Rated short-time withstand current Icw (EF007050)

1.26 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Switching power at 400 V (EF009166)

30 kW

Conditioned rated short-circuit current Iq (EF001444)

100 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/EA/SVB-SW/2HI11 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.