

INDUSTRIAL COMPONENT DATA

P1-32/V/SVB-SW/N 098198 Y7-98198 EATON ELECTRIC Main switch, 3 pole + N, 32 A, STOP function, Lockable in th..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/V/SVB-SW/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/V/SVB-SW/N
Catalog number	Y7-98198
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-831B86718C
Generated	2026-08-04

Product Overview

Main switch, 3 pole + N, 32 A, STOP function, Lockable in the 0 (Off) position, rear mounting

General Switch 3 poles + N 32 A Bottom panel mount Handle

Eaton Moeller® series P1 Main switch, P1, 32 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Mounting method: Rear mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 098198 Model Code P1-32/V/SVB-SW/N EAN 4015080981985 Product Length/Depth 90 mm Product Height 70 mm Product Width 63 mm Product Weight 0.247 kg

Certifications CSA-C22.2 No. 94

IEC/EN 60947

UL

CE

CSA-C22.2 No. 60947-4-1-14

CSA

UL File No.: E36332

VDE 0660

IEC/EN 60204

UL 60947-4-1

UL Category Control No.: NLRV

CSA Class No.: 3211-05

IEC/EN 60947-3

CSA File No.: 012528 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 098198 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

true

Version as maintenance-/service switch (EF006986)

true

Version as safety switch (EF006985)

false

Version as emergency stop installation (EF006959)

false

Version as reversing switch (EF009408)

false

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

13 kW

Rated short-time withstand current Icw (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current Iq (EF001444)

80 kA

Number of poles (EF001391)

4

Number of auxiliary contacts as normally close...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/V/SVB-SW/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.