

INDUSTRIAL COMPONENT DATA

P3-63/V/SVB-SW/N 017517 Y7-17517 EATON ELECTRIC Main switch, 3 pole + N, 63 A, STOP function, Lockable in th..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/V/SVB-SW/N



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/V/SVB-SW/N
Catalog number	Y7-17517
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-F1E1694866
Generated	2026-08-05

Product Overview

Main switch, 3 pole + N, 63 A, STOP function, Lockable in the 0 (Off) position, rear mounting

General Switch 3 poles + N 63 A Bottom panel mount Handle

Main switch, P3, 63 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, Information about equipment supplied: auxiliary contact fitted by user., 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, NEMA12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Main switch, P3, 63 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, Information about equipment supplied: auxiliary contact fitted by user., 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, NEMA12

General specificationsProduct nameEaton Moeller® series P3 Main switchPart

no.P3-63/V/SVB-SW/NEAN4015080175179Product Length/Depth147 millimetreProduct height102 millimetreProduct width90 millimetreProduct weight0.495 kilogramCertificationsUL 60947-4-1

CSA Class No.: 3211-05

CSA File No.: 012528

UL

IEC/EN 60947

UL File No.: E36332

IEC/EN 60947-3

UL Category Control No.: NLRV

IEC/EN 60204

VDE 0660

CSA

CE

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

CSA

ULProduct TradenameP3Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as maintenance-/service switch Version as main switchFitted with:Black rotary handle and locking ringFunctionsSTOP function InterlockableLocking facilityLockable in the 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/V/SVB-SW/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.