

INDUSTRIAL COMPONENT DATA

P3-63/EA/SVB-SW/N/HI11 069724 Y7-69724 EATON ELECTRIC

Main switch, 3 pole + N + 1 N/O + 1 N/C, 63 A, STOP fu..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/EA/SVB-SW/N/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/EA/SVB-SW/N/HI11
Catalog number	Y7-69724
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-6AE786916F
Generated	2026-08-04

Product Overview

Main switch, 3 pole + N + 1 N/O + 1 N/C, 63 A, STOP function, Lockable in the 0 (Off) position, flush mounting

General Switch 3 poles + N + 1 NO + 1 NC 63 A Flush mount

Eaton Eaton Moeller® series P3 Main switch, P3, 63 A, flush mounting, 3 pole + N, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, NEMA12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 Main switch Catalog Number 069724 Model Code P3-63/EA/SVB-SW/N/HI11

EAN 4015080697244 Product Length/Depth 128 mm Product Height 102 mm Product Width 114 mm Product Weight 0.536 kg Certifications UL Listed

CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

UL 60947-4-1
CSA Class No.: 3211-05
CSA File No.: 012528
UL Category Control No.: NLRV
UL File No.: E36332
CSA-C22.2 No. 94
VDE 0660
CE
IEC/EN 60204
IEC/EN 60947-3
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 069724 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
63 A
Rated permanent current at AC-23, 400 V (EF011777)
63 A
Rated permanent current at AC-21, 400 V (EF009165)
63 A
Rated operation power at AC-3, 400 V (EF001364)
30 kW
Rated short-time withstand current Icw (EF007050)
1.26 kA
Rated operation power at AC-23, 400 V (EF007027)
30 kW
Switching power at 400 V (EF009166)
30 kW
Conditioned rated short-circuit current Iq (EF001444)
100 kA
Number of poles (EF001391)

4

Number of auxiliary contacts as norma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/EA/SVB-SW/N/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.