

## INDUSTRIAL COMPONENT DATA

**T3-2-8324/EA/SVB 008771 Y7-8771 EATON ELECTRIC Main switch, 4 pole, 32 A, Emergency-Stop function, 90 °, flu..**

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8324/EA/SVB



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T3-2-8324/EA/SVB    |
| Catalog number  | Y7-8771             |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-AE995FCEFC       |
| Generated       | 2026-08-05          |

**Product Overview**

Main switch, 4 pole, 32 A, Emergency-Stop function, 90 °, flush mounting

General Switch 4 poles 32 A 90° Flush mount Handle

Eaton Moeller® series T3 Main switch, T3, 32 A, flush mounting, 2 contact unit(s), 4 pole, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 4 pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series T3 Main switch Catalog Number 008771 Model Code T3-2-8324/EA/SVB EAN 4015080087717 Product Length/Depth 116 mm Product Height 74 mm Product Width 65 mm Product Weight 0.204 kg

Certifications UL Category Control No.: NLRV

VDE 0660

CSA

CSA File No.: 012528

UL 60947-4-1  
IEC/EN 60947-3  
CE  
CSA-C22.2 No. 60947-4-1-14  
IEC/EN 60204  
IEC/EN 60947  
UL File No.: E36332  
UL  
CSA Class No.: 3211-05  
CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 008771 Low-voltage industrial controls and switchgear (EC000216)  
Feature Name  
Feature Value  
Version as main switch (EF006981)  
Yes  
Version as maintenance-/service switch (EF006986)  
Yes  
Version as safety switch (EF006985)  
No  
Version as emergency stop installation (EF006959)  
Yes  
Version as reversing switch (EF009408)  
No  
Number of switches (EF005586)  
1  
Rated operating voltage (EF001435)  
690 V  
Rated permanent current Iu (EF001389)  
32 A  
Rated permanent current at AC-21, 400 V (EF009165)  
32 A  
Rated operation power at AC-3, 400 V (EF001364)  
11 kW  
Rated short-time withstand current Icw (EF007050)  
0.65 kA  
Rated operation power at AC-23, 400 V (EF007027)  
15 kW  
Switching power at 400 V (EF009166)  
15 kW  
Conditioned rated short-circuit current Iq (EF001444)  
1 kA  
Number of poles (EF001391)  
4  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0

Number of auxiliary contacts...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8324/EA/SVB with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.