

INDUSTRIAL COMPONENT DATA

T3-4-8343/V/SVB 020590 Y7-20590 EATON ELECTRIC P & T switches

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-8343/V/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-8343/V/SVB
Catalog number	Y7-20590
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9132212CCF
Generated	2026-08-05

Product Overview

P & T switches

General Switch; 7 poles; 32 A; 90 °; Panel bottom mounting; Handle

Main switch, T3, 32 A, rear mounting, 4 contact unit(s), 7-pole, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 7-pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, T3, 32 A, rear mounting, 4 contact unit(s), 7-pole, Emergency switching off function, With red rotary handle and yellow locking ring
Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 7-pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specifications
Product name Eaton Moeller® series T3 Main switch
Part

no.T3-4-8343/V/SVBEAN4015080205906Product Length/Depth156 millimetreProduct height74 millimetreProduct width65 millimetreProduct weight0.333 kilogramCertificationsUL

UL 60947-4-1

UL File No.: E36332

UL Category Control No.: NLRV

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

CSA-C22.2 No. 94

VDE 0660

IEC/EN 60947-3

CSA File No.: 012528

CSA

CE

CSA Class No.: 3211-05

UL

CSAProduct TradenameT3Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as emergency stop installation

Version as maintenance-/service switch

Version as main switchFitted with:Red rotary handle and yellow locking ringFunctionsEmergency switching off function

InterlockableNumber of poles7General...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-8343/V/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.