

INDUSTRIAL COMPONENT DATA

T0-4-8344/EA/SVB 008267 Y7-8267 EATON ELECTRIC Main switch, 8-pole, 20 A, Emergency-Stop function, 90 °, Loc..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-8344/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-8344/EA/SVB
Catalog number	Y7-8267
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-69547748F4
Generated	2026-08-04

Product Overview

Main switch, 8-pole, 20 A, Emergency-Stop function, 90 °, Lockable in the 0 (Off) position, flush mounting

General Switch 8 poles 20 A 90° Flush mount Handle

Eaton Moeller® series T0 Main switch, T0, 20 A, flush mounting, 4 contact unit(s), 8-pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function:

Emergency switching off function, With red rotary handle and yellow locking ring, 8-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Main switch Catalog Number 008267 Model Code T0-4-8344/EA/SVB EAN

4015080082675 Product Length/Depth 130 mm Product Height 74 mm Product Width 65 mm Product Weight 0.166 kg

Certifications CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CSA Class No.: 3211-05

CSA File No.: 012528

UL
VDE 0660
CSA
IEC/EN 60204
CE
IEC/EN 60947-3
IEC/EN 60947
UL File No.: E36332
UL Category Control No.: NLRV
CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 008267 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
20 A
Rated permanent current at AC-21, 400 V (EF009165)
20 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW
Rated short-time withstand current Icw (EF007050)
0.32 kA
Rated operation power at AC-23, 400 V (EF007027)
5.5 kW
Switching power at 400 V (EF009166)
5.5 kW
Conditioned rated short-circuit current Iq (EF001444)
6 kA
Number of poles (EF001391)
8
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0

Number of auxiliary conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-8344/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.