

INDUSTRIAL COMPONENT DATA

T3-5-8345/EA/SVB 003170 Y7-3170 EATON ELECTRIC Main switch, 9-pole, 32 A, Emergency-Stop function, 90 °, flu..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-8345/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-8345/EA/SVB
Catalog number	Y7-3170
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-033C8FC3FA
Generated	2026-08-04

Product Overview

Main switch, 9-pole, 32 A, Emergency-Stop function, 90 °, flush mounting

General Switch 9 poles 32 A 90° Flush mount Handle

Main switch, T3, 32 A, flush mounting, 5 contact unit(s), 9-pole, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 9-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, T3, 32 A, flush mounting, 5 contact unit(s), 9-pole, Emergency switching off function, With red rotary handle and yellow locking ring
Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 9-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specifications
Product name Eaton Moeller® series T3 Main switch
Part

no.T3-5-8345/EA/SVBEAN4015080031703Product Length/Depth150 millimetreProduct height74 millimetreProduct width65 millimetreProduct weight0.322 kilogramCertificationsCE

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

VDE 0660

UL 60947-4-1

UL

CSA File No.: 012528

UL Category Control No.: NLRV

UL File No.: E36332

IEC/EN 60947

IEC/EN 60947-3

CSA

CSA-C22.2 No. 94

IEC/EN 60204

CSA

ULProduct TradenameT3Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as main switch

Version as emergency stop installation

Version as maintenance-/service switchFitted with:Red rotary handle and yellow locking ringFunctionsInterlockable

Emergency switching off functionNumber of poles9Gene...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-8345/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.