

INDUSTRIAL COMPONENT DATA

T3-1-8200/I2/SVB 207200 Y7-207200 EATON ELECTRIC Main switch, 1 pole, 32 A, Emergency-Stop function, 90 °, L..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-8200/I2/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T3-1-8200/I2/SVB
Catalog number	Y7-207200
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9DF8D43090
Generated	2026-08-06

Product Overview

Main switch, 1 pole, 32 A, Emergency-Stop function, 90 °, Lockable in the 0 (Off) position, surface mounting

T3-1-8200/I2/SVB

Main switch, T3, 32 A, surface mounting, 1 contact unit(s), 1 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 1 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, T3, 32 A, surface mounting, 1 contact unit(s), 1 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) positionMain switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 1 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3
General specificationsProduct nameEaton Moeller® series T3 Main switchPart

no.T3-1-8200/I2/SVB EAN4015082072001 Product Length/Depth 185 millimetre Product height 124 millimetre Product width 108 millimetre Product weight 0.485 kilogram Certifications UL 60947-4-1

CSA-C22.2 No. 94

IEC/EN 60204

UL File No.: E36332

VDE 0660

CSA Class No.: 3211-05

CE

CSA File No.: 012528

UL

CSA

IEC/EN 60947

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

CSA

UL Product Tradename T3 Product Type Main switch Product Sub Type None Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second Features & Functions Features Version as maintenance-/service switch Version as main switch

Version as emergency stop installation Fitted with: Red rotary handle and yellow locking ri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-8200/I2/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.