

INDUSTRIAL COMPONENT DATA

P1-25/I2H/SVB/N 227860 Y7-227860 EATON ELECTRIC Main switch, 3 pole + N, 25 A, Emergency-Stop function, Lock..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/I2H/SVB/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/I2H/SVB/N
Catalog number	Y7-227860
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-EF55EE1235
Generated	2026-08-05

Product Overview

Main switch, 3 pole + N, 25 A, Emergency-Stop function, Lockable in the 0 (Off) position, surface mounting, hard knockout version

P1-25/I2H/SVB/N

Main switch, P1, 25 A, surface mounting, 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position, hard knockout version

Main switch, P1, Rated uninterrupted current (Iu): 25 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Surface mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, P1, 25 A, surface mounting, 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position, hard knockout version
Main switch, P1, Rated uninterrupted current (Iu): 25 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Surface mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

General specifications
Product name Eaton Moeller® series P1 Main switch
Part

no. P1-25/I2H/SVB/NEAN4015082278601
Product Length/Depth 115 millimetre
Product height 180 millimetre
Product width 100 millimetre
Product weight 0.558 kilogram
Certifications UL Category Control No.: NLRV

CSA File No.: 012528

UL File No.: E36332

UL

CSA

CSA-C22.2 No. 94

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

CE

IEC/EN 60947

VDE 0660

IEC/EN 60204

UL 60947-4-1

CSA

ULProduct TradenameP1Product TypeMain switchProduct Sub TypeNoneCatalog Noteshard knockout version

Rated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as maintenance-/service switch

Version as emergency stop installation

Version as main switchFitted with:Red rotary handle and yellow locking ringFunctionsInterlockable

Emergency switching off functionLocking facilityLockable in the 0 (Off) positionNumber of poles4General informationAccessoriesAuxiliary contact fitted by user.Degree of p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/I2H/SVB/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.