

INDUSTRIAL COMPONENT DATA

T0-2-8900/I1/SVB 207151 Y7-207151 EATON ELECTRIC Main switch, 3 pole + N, 20 A, Emergency-Stop function, 90 ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8900/I1/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8900/I1/SVB
Catalog number	Y7-207151
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-4C7233DF8C
Generated	2026-08-06

Product Overview

Main switch, 3 pole + N, 20 A, Emergency-Stop function, 90 °, Lockable in the 0 (Off) position, surface mounting
T0-2-8900/I1/SVB

Main switch, T0, 20 A, surface mounting, 2 contact unit(s), 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Main switch, T0, 20 A, surface mounting, 2 contact unit(s), 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position
Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

General specifications
Product name Eaton Moeller® series T0 Main switch
Part no. T0-2-8900/I1/SVBEAN4015082071516
Product Length/Depth 137 millimetre
Product height 110 millimetre
Product width 80 millimetre
Product weight 0.361 kilogram
Certifications VDE 0660
IEC/EN 60204
IEC/EN 60947-3
IEC/EN 60947
Product Tradename T0
Product Type Main switch
Product Sub Type None
Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
Features & Functions Features Version as main switch
Version as maintenance-/service switch
Version as emergency stop installation
Fitted with: Red rotary handle and yellow locking ring
Functions Interlockable
Emergency switching off function
Locking facility Lockable in the 0 (Off) position
Number of poles 3
General information Degree of protection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8900/I1/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.