

INDUSTRIAL COMPONENT DATA

P3-63/I4/SVB-SW/N/HI11 207347 Y7-207347 EATON ELECTRIC Main switch, 3 pole + N + 1 N/O + 1 N/C, 63 A, STOP f..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/I4/SVB-SW/N/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/I4/SVB-SW/N/HI11
Catalog number	Y7-207347
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C954B920D6
Generated	2026-08-06

Product Overview

Main switch, 3 pole + N + 1 N/O + 1 N/C, 63 A, STOP function, Lockable in the 0 (Off) position, surface mounting
P3-63/I4/SVB-SW/N/HI11

Eaton Moeller® series P3 Main switch, P3, 63 A, surface mounting, 3 pole + N, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 Main switch Catalog Number 207347 Model Code P3-63/I4/SVB-SW/N/HI11 EAN 4015082073473 Product Length/Depth 139 mm Product Height 240 mm Product Width 160 mm Product Weight 1.135 kg
Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05

IEC 60947

UL 508

EN 60947-3

VDE

IEC/EN 60947

IEC/EN 60204

UL

CSA

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

CSA File No.: 012528

UL 60947-4-1

VDE 0660

CSA-C22.2 No. 94

IEC/EN 60947-3

UL Category Control No.: NLRV

CE

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 207347 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

63 A

Rated permanent current at AC-23, 400 V (EF011777)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Rated short-time withstand current I_{cw} (EF007050)

1.26 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Switching power at 400 V (EF009166)

30 kW

Conditioned rated short-circuit current I_q (EF001444)
100....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/I4/SVB-SW/N/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.