

INDUSTRIAL COMPONENT DATA

T3-2-8324/I2/SVB 218994 Y7-218994 EATON ELECTRIC Main switch, 4 pole, 32 A, Emergency-Stop function, 90 °, s..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8324/I2/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-8324/I2/SVB
Catalog number	Y7-218994
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-62AE216867
Generated	2026-08-05

Product Overview

Main switch, 4 pole, 32 A, Emergency-Stop function, 90 °, surface mounting

T3-2-8324/I2/SVB

Eaton Moeller® series T3 Main switch, T3, 32 A, surface mounting, 2 contact unit(s), 4 pole, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 4 pole, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Main switch Catalog Number 218994 Model Code T3-2-8324/I2/SVB EAN 4015082189945 Product Length/Depth 185 mm Product Height 124 mm Product Width 108 mm Product Weight 0.484 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 94

UL Category Control No.: NLRV

CE

UL
CSA
IEC/EN 60204
UL 60947-4-1
UL File No.: E36332
VDE 0660
IEC/EN 60947-3
IEC/EN 60947
CSA-C22.2 No. 60947-4-1-14
CSA Class No.: 3211-07 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 218994 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
32 A
Rated permanent current at AC-23, 400 V (EF011777)
32 A
Rated permanent current at AC-21, 400 V (EF009165)
32 A
Rated operation power at AC-3, 400 V (EF001364)
11 kW
Rated short-time withstand current I_{cw} (EF007050)
0.65 kA
Rated operation power at AC-23, 400 V (EF007027)
15 kW
Switching power at 400 V (EF009166)
15 kW
Conditioned rated short-circuit current I_q (EF001444)
1 kA
Number of poles (EF001391)
4
Number of auxiliary contacts as normally closed contact (EF001377)
0

Number of auxiliary contacts as norma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8324/I2/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.