

**INDUSTRIAL COMPONENT DATA**

# T3-3-8342/I2/SVB-SW 207209 Y7-207209 EATON ELECTRIC

## Main switch, 6 pole, 32 A, STOP function, 90 °, Lockable..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-8342/I2/SVB-SW



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T3-3-8342/I2/SVB-SW |
| Catalog number  | Y7-207209           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-D5BB0ADA8C       |
| Generated       | 2026-08-06          |

### Product Overview

Main switch, 6 pole, 32 A, STOP function, 90 °, Lockable in the 0 (Off) position, surface mounting

T3-3-8342/I2/SVB-SW

Eaton Moeller® series T3 Main switch, T3, 32 A, surface mounting, 3 contact unit(s), 6 pole, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: STOP function, With black rotary handle and locking ring, 6 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

### Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Main switch Catalog Number 207209 Model Code T3-3-8342/I2/SVB-SW EAN 4015082072094 Product Length/Depth 181 mm Product Height 135 mm Product Width 100 mm Product Weight 0.585 kg

Certifications VDE 0660

CSA Class No.: 3211-05

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

CSA  
IEC/EN 60947  
CE  
CSA-C22.2 No. 94  
IEC/EN 60204  
IEC/EN 60947-3  
UL 60947-4-1  
UL Category Control No.: NLRV  
UL File No.: E36332  
UL Catalog Notes Rated Short-time Withstand Current (I<sub>cs</sub>) for a time of 1 second  
ETIM for 207209 Low-voltage industrial controls and switchgear (EC000216)  
Feature Name  
Feature Value  
Version as main switch (EF006981)  
Yes  
Version as maintenance-/service switch (EF006986)  
Yes  
Version as safety switch (EF006985)  
No  
Version as emergency stop installation (EF006959)  
No  
Version as reversing switch (EF009408)  
No  
Number of switches (EF005586)  
1  
Rated operating voltage (EF001435)  
690 V  
Rated permanent current I<sub>n</sub> (EF001389)  
32 A  
Rated permanent current at AC-23, 400 V (EF011777)  
32 A  
Rated permanent current at AC-21, 400 V (EF009165)  
32 A  
Rated operation power at AC-3, 400 V (EF001364)  
11 kW  
Rated short-time withstand current I<sub>cs</sub> (EF007050)  
0.65 kA  
Rated operation power at AC-23, 400 V (EF007027)  
15 kW  
Switching power at 400 V (EF009166)  
15 kW  
Conditioned rated short-circuit current I<sub>q</sub> (EF001444)  
1 kA  
Number of poles (EF001391)  
6  
Number of auxiliary contacts as normally closed contact (EF001377)  
0

Number of auxiliary contacts as nor...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-8342/I2/SVB-SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.