

INDUSTRIAL COMPONENT DATA

T5B-4-15164/I4/SVB-SW 225386 Y7-225386 EATON ELECTRIC

Main switch, 6 pole + 1 N/O + 1 N/C, 63 A, STOP functi..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-15164/I4/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-4-15164/I4/SVB-SW
Catalog number	Y7-225386
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-92DC0CF6BE
Generated	2026-08-06

Product Overview

Main switch, 6 pole + 1 N/O + 1 N/C, 63 A, STOP function, 90 °, surface mounting

T5B-4-15164/I4/SVB-SW

Eaton Moeller® series T5B Main switch, T5B, 63 A, surface mounting, 4 contact unit(s), 6 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5B, Stop Function: STOP function, With black rotary handle and locking ring, 6 pole, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Main switch Catalog Number 225386 Model Code T5B-4-15164/I4/SVB-SW EAN 4015082253868 Product Length/Depth 240 mm Product Height 197 mm Product Width 160 mm Product Weight 1.49 kg

Certifications CE

IEC/EN 60947

IEC/EN 60204

CSA File No.: 012528

UL

UL 60947-4-1
IEC/EN 60947-3
CSA-C22.2 No. 94
UL File No.: E36332
VDE 0660
CSA
CSA Class No.: 3211-07
UL Category Control No.: NLRV
CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 225386 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
63 A
Rated permanent current at AC-23, 400 V (EF011777)
63 A
Rated permanent current at AC-21, 400 V (EF009165)
63 A
Rated operation power at AC-3, 400 V (EF001364)
22 kW
Rated short-time withstand current Icw (EF007050)
1.3 kA
Rated operation power at AC-23, 400 V (EF007027)
30 kW
Switching power at 400 V (EF009166)
30 kW
Conditioned rated short-circuit current Iq (EF001444)
2 kA
Number of poles (EF001391)
6
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as no...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-15164/I4/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.