

INDUSTRIAL COMPONENT DATA

P1-32/ST/SVB-SW 201715 EATON ELECTRIC Main switch, +steel enclosure, 3p, 32A, handle black, lockable

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/ST/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/ST/SVB-SW
Catalog number	201715
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5FD181D82C
Generated	2026-08-05

Product Overview

Main switch, +steel enclosure, 3p, 32A, handle black, lockable

General Switch; 3 poles; 32A; handle black; Box mounting; Black Handle; Lockable in position 0 (OFF) made of steel

Main switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/32A in the steel sheet enclosure, degree of protection Front IP65, handle black with black locking collar, lockable with 3 padlocks, switch-disconnectors P1 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, center mounting, rear mounting, IVS service distribution board mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, +steel enclosure, 3p, 32A, handle black, lockable Main switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/32A in the steel sheet enclosure, degree of protection Front IP65, handle black with black locking collar, lockable with 3 padlocks, switch-disconnectors P1 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, centre mounting, rear mounting, IVS service distribution board mounting Technical data ETIM 4.0

Version as switch disconnecter compact Yes Version as main switch Yes Version as maintenance-/service switch Yes
Version as safety switch No Version as emergency stop installation No Max. rated operation voltage Ue AC 690 V Rated permanent current Iu 32 A Rated operation power AC-3, 400 V 13 kW Rated operation power at AC-23, 400V 15 kW

Conditioned rated short-circuit current Iq 0 kA Number of poles 3 Number of auxiliary contacts as normally closed contact 0
Number of auxiliary contacts as normally open contact 0 Number of auxiliary contacts as change-over contact 0 Motor drive
optional No Motor drive integrated No Voltage release optional No Device construction Built-in device fixed built-in
technique Suitable for ground mounting No Suitable for front mounting No Suitable for front mounting center No Suitable for
distribution board installation No Suitable for int...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/ST/SVB-SW with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.