

INDUSTRIAL COMPONENT DATA

Matrix 1-3h CGLine+ IP65 40071777003 EATON ELECTRIC

Matrix 1-3h CGLine+ IP65

Brand: EATON - MOELLER | Manufacturer Part Number: Matrix 1-3h CGLine+ IP65



Manufacturer	EATON - MOELLER
MPN / Reference	Matrix 1-3h CGLine+ IP65
Catalog number	40071777003
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-4D98771AC4
Generated	2026-08-06

Product Overview

Matrix 1-3h CGLine+ IP65

Eaton Matrix CGLine+, Exit sign for Adaptive Evacuation Systems AE-CGL+, Increased affordance functionality, 20m viewing distance, CGLine + technology, LED, Maintained operation, IP65, 100lm, 1h/3h selectable duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

Additional Product Information

ETIM for 40071777003 Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)
Lithium-ions
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
138
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Diffuser
Rated life time L70/B50 at 25 °C (EF011870)
50000 h
Degree of protection (IP) (EF005474)
IP65
Impact strength (EF004293)
IK07
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
6.6 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
7 lm
Luminous flux in standby mode (EF011954)
100 lm
Colour temperature (EF009346)
5800 K
Power factor (EF025740)

0.5

Recognition distance (EF008732)

20 m

Nominal operation time (EF012518)

1 h

Width (EF000008)

43 mm

He...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Matrix 1-3h CGLine+ IP65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.