

INDUSTRIAL COMPONENT DATA

LS4-XB 106860 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Devices Switching Devices

Brand: EATON - MOELLER | Manufacturer Part Number: LS4-XB



Manufacturer	EATON - MOELLER
MPN / Reference	LS4-XB
Catalog number	106860
Category	Actuator for position switch with separate actuator
Minimum order	1 Pcs
Document ID	EO-C22574B5E7
Generated	2026-08-03

Product Overview

Industrial Automation Bussines and Industrial Control Devices Switching Devices

LS4-XB

Actuator, form XB

Actuator, Basic function: actuators, Part group reference: LS(4)...ZB, Function: Flat actuator, With the actuator inserted, the N/O contact is open and the NC contact is closed., For use with: LS4...ZB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Position Switches

Additional Product Information

Actuator, form XBActuator, Basic function: actuators, Part group reference: LS(4)...ZB, Function: Flat actuator, With the actuator inserted, the N/O contact is open and the NC contact is closed., For use with: LS4...ZBDelivery program

Basic functionactuatorsPart group referenceLS(4)...ZBFunctionFlat actuatorDescriptionWith the actuator inserted, the N/O contact is open and the NC contact is closed.For use withLS4...ZBTechnical data

GeneralStandardsIEC/EN 60947Climatic proofingDamp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30Mounting positionAs requiredTerminal capacitiesSolid1 x (0.75 - 2.5)
2 x (0.75 - 1.5) mm2Terminal capacitiesFlexible with ferrule1 x (0.5 - 1.5)
2 x (0.5 - 1.5) mm2Repetition accuracy0.02 mmContacts/switching capacityRated impulse withstand voltage [Uimp]6000 V
ACRated insulation voltage [Ui]500 VRated operational current [Ie]AC-1524 V [Ie]10 ARated operational current
[Ie]AC-15220 V 230 V 240 V [Ie]6 ARated operational current [Ie]AC-15380 V 400 V 415 V [Ie]4 ARated operational current
[Ie]DC-1324 V [Ie]3 ARated operational current [Ie]DC-13110 V [Ie]0.8 ARated operational current [Ie]DC-13220 V [Ie]0.3

ASupply frequencymax. 400 HzShort-circuit rating to IEC/EN 60947-5-1max. fuse6 A gG/gLMechanical
variablesMechanical shock resistance (half-sinusoidal shock, 20 ms)Standard-action contact25 gOperating frequency
[Operations/h]? 1800Design verification as per IEC/EN 61439
Technical data for design verificationRated operational current f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS4-XB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.