

INDUSTRIAL COMPONENT DATA

GSMJ240 Medium Voltage British Standard EATON ELECTRIC Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 18..

Brand: EATON - MOELLER | Manufacturer Part Number: GSMJ240



Manufacturer	EATON - MOELLER
MPN / Reference	GSMJ240
Catalog number	Medium Voltage - British Standard
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-536B06080B
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Medium Voltage - British Standard

GSMJ 240A 800V AC FUSE LINK- SFE8340240 - Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Fuse, Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 180 mm, aR, BS, ultra rapid, offset bolted tags, Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Special Bussmann series fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 180 mm, aR, BS, ultra rapid
Fuse, Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 180 mm, aR, BS, ultra rapid, offset bolted tags, Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_N 240 A Rated voltage AC 800

V Construction size BS88 Size 80 x 180 mm Utilization category aR Breaking Capacity 100 kA Usable for

size/applications Protection of semi-conductor devices Release characteristic [class] ultra

rapid Standard/Approval BS Shape offset bolted tags Standards/Regulations BS88-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 240 A Rated voltage 800 V Voltage type AC Rated switching capacity 100

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No
ETIM for GSMJ240 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Rated current (EF000227)
240 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Type of fuse status indicator (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSMJ240 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.