

## INDUSTRIAL COMPONENT DATA

# GSMK120 Medium Voltage British Standard EATON ELECTRIC Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: GSMK120



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | GSMK120                           |
| Catalog number  | Medium Voltage - British Standard |
| Category        | HRC fuse                          |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-949D04BDC7                     |
| Generated       | 2026-08-05                        |

## Product Overview

Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Medium Voltage - British Standard

GSMK 120A 1000V AC FUSE LINK- SFE8350120 - Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Fuse, Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid, offset bolted tags, Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Special Busmann series fuses

## Additional Product Information

Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid  
Fuse, Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid, offset bolted tags, Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA  
Delivery program

Product range Fuse  
Basic function Fuse-link  
Field of application high speed  
Rated current [I]<sub>N</sub> 120 A  
Rated voltage AC 1000 V  
Construction size BS88  
Size 80 x 180 mm  
Utilization category aR  
Breaking Capacity 100 kA  
Usable for

size/applications Protection of semi-conductor devices  
Release characteristic [class] ultra

rapid  
Standard/Approval BS  
Shape offset bolted tags  
Standards/Regulations BS88-4  
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)  
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]  
[AFZ800015])Construction sizeOtherRated current120 ARated voltage1000 VVoltage typeACRated switching capacity100  
kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping  
lugs (IMGL)No

ETIM for GSMK120 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

120 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

None

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSMK120 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.