

INDUSTRIAL COMPONENT DATA

GSMK120 Medium Voltage British Standard EATON ELECTRIC Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: GSMK120



Manufacturer	EATON - MOELLER
MPN / Reference	GSMK120
Catalog number	Medium Voltage - British Standard
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-949D04BDC7
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Medium Voltage - British Standard

GSMK 120A 1000V AC FUSE LINK- SFE8350120 - Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Fuse, Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid, offset bolted tags, Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Special Busmann series fuses

Additional Product Information

Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid
Fuse, Fuse-link, high speed, 120 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid, offset bolted tags, Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 120 A
Rated voltage AC 1000 V
Construction size BS88
Size 80 x 180 mm
Utilization category aR
Breaking Capacity 100 kA
Usable for

size/applications Protection of semi-conductor devices
Release characteristic [class] ultra

rapid
Standard/Approval BSS
Shape offset bolted tags
Standards/Regulations BS88-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current120 ARated voltage1000 VVoltage typeACRated switching capacity100
kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping
lugs (IMGL)No

ETIM for GSMK120 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

120 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GSMK120 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.