

INDUSTRIAL COMPONENT DATA

46KBR50 EATON ELECTRIC Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, K fast, style D ter..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KBR50



Manufacturer	EATON - MOELLER
MPN / Reference	46KBR50
Catalog number	10000
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-827B103600
Generated	2026-08-05

Product Overview

46KV 50A REMOVABLE B/H EXPULSION LINK

Expulsion fuse-link, medium voltage, 50 A, AC 46 kV, 787 mm, ANSI, K fast, style BR termination

Fuse, Expulsion fuse-link, medium voltage, 50 A, AC 46 kV, 787 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 46KBR50 EAN 5027590481168
UPC 051712397919 Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 56.4 g

Compliances ANSI C37.42 Electrical data

Amperage Rating 50 A Voltage rating 46 kV Voltage type AC Current characteristic type Type K - Complies with ANSI C
37-42 requirements for fast acting K Characteristics Rated frequency - min 50 Hz Product specification

Construction size 787 mm Standard ANSI Type of termination Removable buttonhead Color Yellow

ETIM for 46KBR50 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

50 A

Rated voltage (EF000228)

46 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

K

Type of termination (EF012540)

Removable buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KBR50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.