

## INDUSTRIAL COMPONENT DATA

# 72KB10 EATON ELECTRIC Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, K fast, style D term..

Brand: EATON - MOELLER | Manufacturer Part Number: 72KB10



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | 72KB10                              |
| Catalog number  | 72KB10                              |
| Category        | Expulsion fuse-link, medium voltage |
| Minimum order   | 25 Pcs                              |
| Document ID     | EO-34CC4A1C88                       |
| Generated       | 2026-08-05                          |

## Product Overview

Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, K fast, style D termination

72KV 10A EXPULSION LINK

72KB10 - Expulsion fuse-link, medium voltage, 10 A, AC 72 kV, 1016 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 10 A, AC 72 kV, 1016 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann fuses

## Additional Product Information

Expulsion fuse-link, medium voltage, 10 A, AC 72 kV, 1016 mm, ANSI, K fast Fuse, Expulsion fuse-link, medium voltage, 10 A, AC 72 kV, 1016 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 10 A Rated voltage AC 72 kV Size 1016 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] K fast Standard/Approval ANSI Standards/Regulations ANSI C37-42

ETIM for 72KB10 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

10 A  
Voltage type (EF000187)  
AC  
Rated frequency (EF001663)  
50 Hz  
Release characteristic (EF000889)  
K  
Type of termination (EF012540)  
Fixed buttonhead  
Standard (EF009322)  
ANSI

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 72KB10 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.