

INDUSTRIAL COMPONENT DATA

72KB30 EATON ELECTRIC Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, K fast, style D term..

Brand: EATON - MOELLER | Manufacturer Part Number: 72KB30



Manufacturer	EATON - MOELLER
MPN / Reference	72KB30
Catalog number	72KB30
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-C308D8AC90
Generated	2026-08-05

Product Overview

Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, K fast, style D termination

72KV 30A EXPULSION LINK

72KB30 - Expulsion fuse-link, medium voltage, 30 A, AC 72 kV, 1016 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 30 A, AC 72 kV, 1016 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Expulsion fuse-link, medium voltage, 30 A, AC 72 kV, 1016 mm, ANSI, K fast Fuse, Expulsion fuse-link, medium voltage, 30 A, AC 72 kV, 1016 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 30 A Rated voltage AC 72 kV Size 1016 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] K fast Standard/Approval ANSI Standards/Regulations ANSI C37-42

ETIM for 72KB30 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

30 A
Voltage type (EF000187)
AC
Rated frequency (EF001663)
50 Hz
Release characteristic (EF000889)
K
Type of termination (EF012540)
Fixed buttonhead
Standard (EF009322)
ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 72KB30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.