

INDUSTRIAL COMPONENT DATA

CHM3DUIN-M EATON ELECTRIC MFH 10x38 3 Pole Fuse Ind + 1 Pole N

Brand: EATON - MOELLER | Manufacturer Part Number: CHM3DUIN-M



Manufacturer	EATON - MOELLER
MPN / Reference	CHM3DUIN-M
Catalog number	10000
Category	Holder for cylindrical fuse
Minimum order	3 Pcs
Document ID	EO-8CAE2058E0
Generated	2026-08-06

Product Overview

MFH 10x38 3 Pole Fuse Ind + 1 Pole N

MFH 10x38 3 Pole Fuse Ind + 1 Pole N Fuse holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 3P + N, IEC, with indicator
Fuse-holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 3P + N, IEC, Indicating

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 3P + N, IEC, with indicator Fuse-holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 3P + N, IEC, Indicating, DIN Rail mounting, for cyclindrical fuse links Delivery program

Product range Fuse Basic function Fuse-holder Field of application low voltage Rated current [I]_N 32 A Rated voltage AC 690 V Size 10 x 38 mm Status indicator with indicator Number of poles 3P + N Standard/Approval IEC Standards/Regulations IEC 60269-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse ( [ADI305007]) Nominal voltage 690 V Mounting method DIN rail For fuse size 10x38 mm Number of poles 3 Concurrently switching N-neutral No Lockable No Optical defect indication Yes Width in number of modular spacings 4 Built-in depth 50 mm Degree of protection (IP) IP20

ETIM for CHM3DUIN-M Circuit breakers and fuses (EC002705)

Feature Name

Feature Value

Nominal voltage (EF000002)
690 V
Mounting method (EF000003)
DIN rail
For fuse size (EF008316)
10x38 mm
Number of poles (EF001391)
3
Concurrently switching neutral conductor (EF005997)
No
Lockable (EF000113)
No
With optical defect indication (EF008181)
Yes
Width in number of modular spacings (EF002950)
4
Built-in depth (EF000218)
50 mm
Degree of protection (IP) (EF005474)
IP20

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CHM3DUIN-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.