

INDUSTRIAL COMPONENT DATA

MP2HI3HCGL EATON ELECTRIC Micropoint 2 Hi power 3 Hour NM CGLine

Brand: EATON - MOELLER | Manufacturer Part Number: MP2HI3HCGL



Manufacturer	EATON - MOELLER
MPN / Reference	MP2HI3HCGL
Catalog number	10000
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-E92029C515
Generated	2026-08-04

Product Overview

Micropoint 2 Hi power 3 Hour NM CGLine

Eaton Micropoint 2 High Output, Safety lighting, High output, CGLine + technology, LED, Non-Maintained operation, IP20, 298lm, 3 hour duration, Recessed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

ETIM for MP2HI3HCGL Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Built-in

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
1
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Other
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Focal lens
Degree of protection (IP) (EF005474)
IP20
Impact strength (EF004293)
IK04
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
Yes
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
3.9 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
298 lm
Colour temperature (EF009346)
6200 K
Power factor (EF025740)
0.5
Nominal operation time (EF012518)

3 h
Width (EF000008)
29 mm
Height/depth (EF001456)
3 mm
Length (EF001438)
333 mm
Outer diameter (EF000015)
90 mm
Built-in height/depth (EF023518)
63 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MP2HI3HCGL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.