

INDUSTRIAL COMPONENT DATA

**TM-1-SOND-ERSTBESTELLUNG/EZ 208262 Y7-208262 EATON
ELECTRIC Non-standard switch, TM, 10 A, centre mounting, ..**

Brand: EATON - MOELLER | Manufacturer Part Number: TM-1-SOND-ERSTBESTELLUNG/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	TM-1-SOND-ERSTBESTELLUNG/EZ
Catalog number	Y7-208262
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-B3F3D23045
Generated	2026-08-04

Product Overview

Non-standard switch, TM, 10 A, centre mounting, 1 contact unit(s)

TM-1-SOND-ERSTBESTELLUNG/EZ

Non-standard switch, TM, 10 A, centre mounting, 1 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, TM, 10 A, centre mounting, 1 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first timeNon-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: centre mounting, 1 contact unit(s), Rated uninterrupted current: $I_u = 10\text{ A}$ Delivery program

Product rangeNon-standard switchPart group referenceTMNotescustomized version according to formNon-standard orderTM mini rotary switches, ordering for the first timeDegree of ProtectionFront IP65Designcentre mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]3 kWRated uninterrupted current [I_u]10 ANote on rated uninterrupted current ! I_u Rated uninterrupted current I_{uis} specified for max. cross-section.Number of contact units1 contact unit(s)Design verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [I_n]10 AHeat dissipation per pole, current-dependent [Pvid]0.15 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation,

non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+50 °CIEC/EN 61439 design verification10.2 Strength of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-1-SOND-ERSTBESTELLUNG/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.