

INDUSTRIAL COMPONENT DATA

**TM-1-SOND-ERSTBESTELLUNG/EZ 208262 Y7-208262 EATON
ELECTRIC Non-standard switch, TM, 10 A, centre mounting, ..**

Brand: EATON - MOELLER | Manufacturer Part Number: TM-1-SOND-ERSTBESTELLUNG/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	TM-1-SOND-ERSTBESTELLUNG/EZ
Catalog number	Y7-208262
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-B3F3D23045
Generated	2026-08-06

Product Overview

Non-standard switch, TM, 10 A, centre mounting, 1 contact unit(s)

TM-1-SOND-ERSTBESTELLUNG/EZ

Non-standard switch, TM, 10 A, centre mounting, 1 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, TM, 10 A, centre mounting, 1 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: centre mounting, 1 contact unit(s), Rated uninterrupted current: $I_u = 10\text{ A}$

Delivery program

Product range

Non-standard switch

Part group reference

TM

Notes

customized version according to form

Non-standard

order

TM mini rotary switches, ordering for the first time

Degree of Protection

Front IP65

Design

centre mounting

Motor rating

AC-23A, 50 - 60 Hz [P]400 V [P]3 kW

Rated uninterrupted current [I_u]

10 A

Note on rated uninterrupted current ! I_u

Rated uninterrupted current

I_{uis} specified for max. cross-section.

Number of contact units

1 contact unit(s)

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

10 A

Heat dissipation per pole, current-dependent [P_{vid}]

0.15 W

Equipment heat dissipation, current-dependent [P_{vid}]

0 W

Static heat dissipation,

non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+50 °CIEC/EN 61439 design verification10.2 Strength of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-1-SOND-ERSTBESTELLUNG/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.