

INDUSTRIAL COMPONENT DATA

TM-4-SOND-ERSTBESTELLUNG/EZ 208268 Y7-208268 EATON ELECTRIC Non-standard switch, TM, 10 A, centre mounting, ..

Brand: EATON - MOELLER | Manufacturer Part Number: TM-4-SOND-ERSTBESTELLUNG/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	TM-4-SOND-ERSTBESTELLUNG/EZ
Catalog number	Y7-208268
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-C4614795EB
Generated	2026-08-04

Product Overview

Non-standard switch, TM, 10 A, centre mounting, 4 contact unit(s)

TM-4-SOND-ERSTBESTELLUNG/EZ

Non-standard switch, TM, 10 A, centre mounting, 4 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: center mounting, 4 contact unit(s), Rated uninterrupted current: I_u= 10 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, TM, 10 A, centre mounting, 4 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first timeNon-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: centre mounting, 4 contact unit(s), Rated uninterrupted current: I_u= 10 A

Delivery program
Product rangeNon-standard switchPart group referenceTMNotescustomized version according to formNon-standard orderTM mini rotary switches, ordering for the first timeDegree of ProtectionFront IP65Designcentre mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]3 kWRated uninterrupted current [I_u]10 ANote on rated uninterrupted current !uRated

uninterrupted current I_{uis} specified for max. cross-section. Number of contact units 4 contact unit(s) Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [I_n] 10 A Heat dissipation per pole, current-dependent [P_{vid}] 0.15 W Equipment heat dissipation, current-dependent [P_{vid}] 0 W Static heat dissipation, non-current-dependent [P_{vs}] 0 W Heat dissipation capacity [P_{diss}] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +50 °C IEC/EN 61439 design verification 10.2 Strength of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-4-SOND-ERSTBESTELLUNG/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.