

## INDUSTRIAL COMPONENT DATA

# TM-5-SOND-ERSTBESTELLUNG/EZ 208270 Y7-208270 EATON ELECTRIC Non-standard switch, TM, 10 A, centre mounting, ..

Brand: EATON - MOELLER | Manufacturer Part Number: TM-5-SOND-ERSTBESTELLUNG/EZ



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | EATON - MOELLER             |
| MPN / Reference | TM-5-SOND-ERSTBESTELLUNG/EZ |
| Catalog number  | Y7-208270                   |
| Category        | Control switch              |
| Minimum order   | 1 Pcs                       |
| Document ID     | EO-56FE04FCFE               |
| Generated       | 2026-08-06                  |

## Product Overview

Non-standard switch, TM, 10 A, centre mounting, 5 contact unit(s)

TM-5-SOND-ERSTBESTELLUNG/EZ

Non-standard switch, TM, 10 A, centre mounting, 5 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: center mounting, 5 contact unit(s), Rated uninterrupted current: I<sub>u</sub> = 10 A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

Non-standard switch, TM, 10 A, centre mounting, 5 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time  
Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: centre mounting, 5 contact unit(s), Rated uninterrupted current: I<sub>u</sub> = 10 A  
Delivery program

Product rangeNon-standard switchPart group referenceTMNotescustomized version according to formNon-standard orderTM mini rotary switches, ordering for the first timeDegree of ProtectionFront IP65Designcentre mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]3 kWRated uninterrupted current [I<sub>u</sub>]10 ANote on rated uninterrupted current !uRated

uninterrupted current I<sub>uis</sub> specified for max. cross-section. Number of contact units 5 contact unit(s) Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [I<sub>n</sub>] 10 A Heat dissipation per pole, current-dependent [P<sub>vid</sub>] 0.15 W Equipment heat dissipation, current-dependent [P<sub>vid</sub>] 0 W Static heat dissipation, non-current-dependent [P<sub>vs</sub>] 0 W Heat dissipation capacity [P<sub>diss</sub>] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +50 °C IEC/EN 61439 design verification 10.2 Strength of...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-5-SOND-ERSTBESTELLUNG/EZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.