

INDUSTRIAL COMPONENT DATA

PLN4-C10/1N-MW 263190 Y7-263190 EATON ELECTRIC Over current switch, 10A, 1pole+N, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLN4-C10/1N-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLN4-C10/1N-MW
Catalog number	Y7-263190
Category	Miniature circuit breaker (MCB)
Minimum order	12 Pcs
Document ID	EO-6AB13FB532
Generated	2026-08-06

Product Overview

Over current switch, 10A, 1pole+N, type C characteristic

PLN4-C10/1N-MW

Miniature circuit breaker (MCB), 10 A, 1p+N, characteristic: C

Miniature circuit breaker (MCB), PLN4, 1-pole+N, tripping characteristic: C, rated current In: 10 A, rated switching capacity according to IEC/EN 60898-1: 4.5 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary

Additional Product Information

Miniature circuit breaker (MCB), 10 A, 1p+N, characteristic: CMiniature circuit breaker (MCB), PLN4, 1-pole+N, tripping characteristic: C, rated current In: 10 A, rated switching capacity according to IEC/EN 60898-1: 4.5 kA, Switchgear for residential and commercial applications

General specificationsProduct nameEaton Moeller series xPole - PLN4 MCBPart

no.PLN4-C10/1N-MWEAN4015082631901Product Length/Depth80 millimetreProduct height75 millimetreProduct width17.5 millimetreProduct weight0.112 kilogramCompliancesRoHS conformProduct TradenamexPole - PLN4Product

TypeMCBProduct Sub TypeNoneDelivery programApplicationSwitchgear for residential and commercial applications

xPole - Switchgear for residential and commercial applicationsNumber of polesSingle-pole + NNumber of poles

(total)2Number of poles (protected)1Tripping characteristicCRelease characteristicCAMperage Rating10 ATypeMiniature circuit breaker

PLN4Technical Data - ElectricalVoltage typeACRated operational voltage (Ue) - max230 VRated insulation voltage (Ui)440

VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60898-1)4.5 kARated short-circuit breaking capacity (EN 60898) at 230 V4.5 kARated short-circuit breaking capacity (EN 60898) at 400 V4.5 kARated short-circuit breaking capacity (IEC 60947-2) at 230 V0 kARated short-circuit breaking capacity (IEC 60947-2) at 400 V0 kAOvervoltage categoryIIIPollution degree2Technical Data - MechanicalW...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLN4-C10/1N-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.