

INDUSTRIAL COMPONENT DATA

PLS6-C13/3N-MW 243016 Y7-243016 EATON ELECTRIC Over current switch, 13A, 3pole+N, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLS6-C13/3N-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLS6-C13/3N-MW
Catalog number	Y7-243016
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-98C3093357
Generated	2026-08-06

Product Overview

Over current switch, 13A, 3pole+N, type C characteristic

PLS6-C13/3N-MW

Miniature circuit breaker (MCB), 13 A, 3p+N, characteristic: C

Miniature circuit breaker (MCB), PLS6, 3-pole+N, tripping characteristic: C, rated current In: 13 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Big Home

Additional Product Information

Miniature circuit breaker (MCB), 13 A, 3p+N, characteristic: C
Miniature circuit breaker (MCB), PLS6, 3-pole+N, tripping characteristic: C, rated current In: 13 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

General specificationsProduct nameEaton Moeller series xPole - PLS6/M MCBPart

no.PLS6-C13/3N-MWEAN4015082430160Product Length/Depth85 millimetreProduct height73 millimetreProduct width70 millimetreProduct weight0.456 kilogramCompliancesRoHS conformProduct TradenamexPole - PLS6/MProduct

TypeMCBProduct Sub TypeNoneDelivery programApplicationSwitchgear for residential and commercial applications

xPole - Switchgear for residential and commercial applicationsNumber of polesThree-pole + NNumber of poles

(total)4Number of poles (protected)3Tripping characteristicCRelease characteristicCAmperage Rating13 ATypeMiniature circuit breaker

PLS6Technical Data - ElectricalVoltage typeACRated operational voltage (Ue) - max400 VRated insulation voltage (Ui)440

VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60898-1)6 kARated short-circuit breaking capacity (EN 60898) at 230 V6 kARated short-circuit breaking capacity (EN 60898) at 400 V6 kARated short-circuit breaking capacity (IEC 60947-2) at 230 V0 kARated short-circuit breaking capacity (IEC 60947-2) at 400 V0 kAOvoltage categoryIIIPollution degree2Technical Data - MechanicalWidth in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLS6-C13/3N-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.