

INDUSTRIAL COMPONENT DATA

PLS6-C13/4-MW 243085 Y7-243085 EATON ELECTRIC Over current switch, 13A, 4 p, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLS6-C13/4-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLS6-C13/4-MW
Catalog number	Y7-243085
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-A4331432DC
Generated	2026-08-05

Product Overview

Over current switch, 13A, 4 p, type C characteristic

PLS6-C13/4-MW

Miniature circuit breaker (MCB), 13 A, 4p, characteristic: C

Miniature circuit breaker (MCB), PLS6, 4 pole, tripping characteristic: C, rated current In: 13 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Big Home
--------------	---

Additional Product Information

Miniature circuit breaker (MCB), 13 A, 4p, characteristic: C
Miniature circuit breaker (MCB), PLS6, 4 pole, tripping characteristic: C, rated current In: 13 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

General specifications
Product name Eaton Moeller series xPole - PLS6/M MCB

Part no. PLS6-C13/4-MW EAN 4015082430856
Product Length/Depth 85 millimetre
Product height 73 millimetre
Product width 70 millimetre
Product weight 0.48 kilogram

Compliance RoHS conform
Product Trade name xPole - PLS6/M

Product Type MCB
Product Sub Type None
Delivery program Application Switchgear for residential and commercial applications

xPole - Switchgear for residential and commercial applications
Number of poles Four-pole
Number of poles (total) 4
Number of poles (protected) 4
Tripping characteristic C
Release characteristic CA

Amperage Rating 13 A
Type Miniature circuit breaker
PLS6
Technical Data - Electrical
Voltage type AC
Rated operational voltage (Ue) - max 400 V
Rated insulation voltage (Ui) 440 V
Rated impulse withstand voltage (Uimp) 4 kV
Frequency rating - min 50 Hz
Frequency rating - max 60 Hz
Rated switching

capacity (IEC/EN 60898-1)6 kARated short-circuit breaking capacity (EN 60898) at 230 V6 kARated short-circuit breaking capacity (EN 60898) at 400 V6 kARated short-circuit breaking capacity (IEC 60947-2) at 230 V0 kARated short-circuit breaking capacity (IEC 60947-2) at 400 V0 kAOvervoltage categoryIIIPollution degree2Technical Data - MechanicalWidth in number of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLS6-C13/4-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.