

INDUSTRIAL COMPONENT DATA

PLS6-C13-MW 242679 Y7-242679 EATON ELECTRIC Over current switch, 13A, 1p, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLS6-C13-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLS6-C13-MW
Catalog number	Y7-242679
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-6394D1B14C
Generated	2026-08-03

Product Overview

Over current switch, 13A, 1p, type C characteristic

PLS6-C13-MW

Miniature circuit breaker (MCB), 13 A, 1p, characteristic: C

Miniature circuit breaker (MCB), PLS6, 1-pole, tripping characteristic: C, rated current In: 13 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Residential Switchgear
--------------	--

Additional Product Information

Miniature circuit breaker (MCB), 13 A, 1p, characteristic: C
Miniature circuit breaker (MCB), PLS6, 1-pole, tripping characteristic: C, rated current In: 13 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

General specifications
Product name Eaton Moeller series xPole - PLS6/M MCB

Part no. PLS6-C13-MW
EAN 4015082426798
Product Length/Depth 85 millimetre
Product height 73 millimetre
Product width 17.5 millimetre
Product weight 0.12 kilogram
Compliance RoHS conform
Certifications CE
Product Trade name xPole -

PLS6/M
Product Type MCB
Product Sub Type None
Delivery program Application Switchgear for residential and commercial applications

xPole - Switchgear for residential and commercial applications
Number of poles Single-pole
Number of poles (total) 1
Number of poles (protected) 1
Tripping characteristic C
Release characteristic CA
Mperage Rating 13 A
Type Miniature circuit breaker
PLS6
Technical Data - Electrical
Voltage type AC
Rated operational voltage (Ue) - max 230 V
Rated insulation voltage (Ui) 440

VRated impulse withstand voltage (Uimp)4 kVFrequency rating - min50 HzFrequency rating - max60 HzRated switching capacity (IEC/EN 60898-1)6 kARated short-circuit breaking capacity (EN 60898) at 230 V6 kARated short-circuit breaking capacity (EN 60898) at 400 V6 kARated short-circuit breaking capacity (IEC 60947-2) at 230 V0 kARated short-circuit breaking capacity (IEC 60947-2) at 400 V0 kAOvervoltage categoryIIIPollution degree2Technical Data - MechanicalW...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLS6-C13-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.