

INDUSTRIAL COMPONENT DATA

PLS6-C16/4-MW 243087 Y7-243087 EATON ELECTRIC Over current switch, 16A, 4 p, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLS6-C16/4-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLS6-C16/4-MW
Catalog number	Y7-243087
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-53AE941A18
Generated	2026-08-05

Product Overview

Over current switch, 16A, 4 p, type C characteristic

PLS6-C16/4-MW

Eaton Moeller series xPole - PLS6/M MCB. PLS6, 4 pole, tripping characteristic: C, rated current In: 16 A, rated switching capacity IEC/EN 60898-1: 6 kA

Miniature circuit breaker (MCB), PLS6, 4 pole, tripping characteristic: C, rated current In: 16 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Big Home
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - PLS6/M MCB

Catalog Number 243087

Model Code PLS6-C16/4-MW

EAN 4015082430870

Product Length/Depth 85 mm

Product Height 73 mm

Product Width 70 mm

Product Weight 0.48 kg

Compliances RoHS conform

Delivery program

Application Switchgear for residential and commercial applications

xPole - Switchgear for residential and commercial applications

Number of poles Four-pole

Number of poles (total) 4

Number of poles (protected) 4

Tripping characteristic C

Release characteristic C

Amperage Rating 16 A

Type Miniature circuit breaker

PLS6

Technical Data - Electrical

Voltage type AC

Rated operational voltage (Ue) - max 400 V

Rated insulation voltage (Ui) 440 V

Rated impulse withstand voltage (Uimp) 4 kV

Frequency rating - min 50 Hz

Frequency rating - max 60 Hz

Rated switching capacity (IEC/EN 60898-1) 6 kA

Overvoltage category III

Pollution degree 2

Technical Data - Mechanical

Width in number of modular spacings 4

Built-in depth 70.5 mm

Degree of protection IP20

Connectable conductor cross section (solid-core) - min 1 mm²

Connectable conductor cross section (solid-core) - max 25 mm²

Connectable conductor cross section (multi-wired) - min 1 mm²

Connectable conductor cross section (multi-wired) - max 25 mm²

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In) 16 A

Heat dissipation per pole, current-dependent 0 W

Equipment heat dissipation, current-dependent 8.8 W

S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLS6-C16/4-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.