

INDUSTRIAL COMPONENT DATA

PLS6-D50/3 113406 Y7-113406 EATON ELECTRIC Over current switch, 50A, 3 p, type D characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLS6-D50/3



Manufacturer	EATON - MOELLER
MPN / Reference	PLS6-D50/3
Catalog number	Y7-113406
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-21379DC67D
Generated	2026-08-03

Product Overview

Over current switch, 50A, 3 p, type D characteristic

PLS6-D50/3

Eaton Moeller series xPole - PLS6/M MCB. PLS6, 3-poles, tripping characteristic: D, rated current In: 50 A

Miniature circuit breaker (MCB), PLS6, 3-poles, tripping characteristic: D, rated current In: 50 A, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - PLS6/M MCB Catalog Number 113406 Model Code PLS6-D50/3 EAN

4015081129515 Product Length/Depth 85 mm Product Height 73 mm Product Width 52.5 mm Product Weight 0.36 kg

Compliances RoHS conform Delivery program

Number of poles (total) 3 Number of poles (protected) 3 Release characteristic D Amperage Rating 50 A Technical data - electrical

Voltage type AC Rated operational voltage (Ue) - max 400 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated short-circuit breaking capacity (EN 60898) at 230 V 6 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 6 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 0 kA Overvoltage category III

Pollution degree 2 Technical data - mechanical

Width in number of modular spacings 3 Built-in depth 70.5 mm Degree of protection IP20 Connectable conductor cross section (solid-core) - min 1 mm² Connectable conductor cross section (solid-core) - max 25 mm² Connectable conductor cross section (multi-wired) - min 1 mm² Connectable conductor cross section (multi-wired) - max 25 mm² Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In) 50 A Heat dissipation per pole, current-dependent 0 W Static heat dissipation, non-current-dependent 0 W Heat dissipation, non-current-dependent 0 W Heat dissipation, non-current-dependent 0 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLS6-D50/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.