

INDUSTRIAL COMPONENT DATA

PLZ6-B15/1N-MW 242784 EATON ELECTRIC Over current switch, 15A, 1pole+N, type B characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLZ6-B15/1N-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLZ6-B15/1N-MW
Catalog number	242784
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-8CEC6E3997
Generated	2026-08-06

Product Overview

Over current switch, 15A, 1pole+N, type B characteristic

PLZ6-B15/1N-MW

Miniature circuit breaker (MCB), 15A, 1pole+N, type B characteristic

Miniature circuit breaker (MCB), PLZ6, 1-pole+N, tripping characteristic: B, rated current In: 15 A, rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary
--------------	---

Additional Product Information

Miniature circuit breaker (MCB), 15A, 1pole+N, type B characteristic
Miniature circuit breaker (MCB) PLZ6, 1 pole+N,
Tripping characteristic: B, Rated current In: 15 A, Rated switching capacity according to IEC/EN 60898-1: 6 kA, Switchgear for residential and commercial applications
Delivery program

Basic function
Miniature circuit-breakers
Number of poles 1 pole+N
Tripping characteristic B
Application Switchgear for residential and commercial applications
Rated current [In] 15 A
Rated switching capacity according to IEC/EN 60898-1 [Icn] 6 kA
Product range PLZ6
Technical data

Electrical
Rated switching capacity according to IEC/EN 60898-1 [Icn] 6 kA
Design verification as per IEC/EN 61439

Technical data for design verification
Rated operational current for specified heat dissipation [In] 15 A
Heat dissipation per pole, current-dependent [Pvid] 0 W
Equipment heat dissipation, current-dependent [Pvid] 2.4 W
Static heat dissipation, non-current-dependent [Pvs] 0 W
Heat dissipation capacity [Pdiss] 0 W
Operating ambient temperature min. -25 °C
Operating ambient temperature max. +75 °C
linear, per +1 °C, results in a 0.5% reduction of current carrying capacity
IEC/EN 61439

design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLZ6-B15/1N-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.