

INDUSTRIAL COMPONENT DATA

E57EAL4T111SP 136239 Y7-136239 EATON ELECTRIC

Proximity switch, inductive, 1N/O, Sn 0.8mm, 3L, 10-30VDC, PNP..

Brand: EATON - MOELLER | Manufacturer Part Number: E57EAL4T111SP



Manufacturer	EATON - MOELLER
MPN / Reference	E57EAL4T111SP
Catalog number	Y7-136239
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-CD9AA5C666
Generated	2026-08-03

Product Overview

Proximity switch, inductive, 1N/O, Sn=0.8mm, 3L, 10-30VDC, PNP, M4mm, line 2m

E57EAL4T111SP

Proximity switch, E57 Miniatur Series, 1 N/O, 3-wire, 10 - 30 V DC, 4 mm, Sn= 0.8 mm, Flush, PNP, Stainless steel, 2 m connection cable

Proximity switch, Inductive Sensors, Product range: E57 Miniature Series, Connection: 3-wire, Design (outer dimensions): 4 mm, Rated operational voltage: Ue= 10 - 30 V DC, Rated switching distance: Sn= 0.8 mm, Type of mounting: Flush, Switching type: PNP, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, Standards: IEC/EN 60947-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E57 Proximity switch Catalog Number 136239 Model Code E57EAL4T111SP EAN 4015081330324 Product Length/Depth 154.94 mm Product Height 48.26 mm Product Width 127 mm Product Weight 0.07 kg Certifications IEC/EN 60947-5

CE Product specifications

Type Inductive sensor Electric connection type Cable Enclosure material finishing Other Actuation type Metallic Target

Enclosure material Metal Enclosure type Cylinder plain Category (EN 954-1) B Explosion safety category for dust None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Diameter sensor 4 mm Number of contact energized outputs with signalling function 0 Number of contacts (normally open contacts) 1 Number of outputs (protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 10 A Output current at protected output - max 0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Functions Short-circuit protection Voltage type DC Mounting method Flush mounting Material Stainless steel Connection type 2 m connection cable 3-wire Installation type Concise Degree of protection IP67 NEMA 6P Interface type None LED indicator Status indication of Switching state: Red LED Switch function type Normally...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57EAL4T111SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.