

INDUSTRIAL COMPONENT DATA

XC-CPU101-FC128K-8DI-6DO 289169 XC-CPU101-FC128K EATON ELECTRIC Modular PLC, 24 V DC, 8DI, 6DO, RS232, optic..

Brand: EATON - MOELLER | Manufacturer Part Number: XC-CPU101-FC128K-8DI-6DO



Manufacturer	EATON - MOELLER
MPN / Reference	XC-CPU101-FC128K-8DI-6DO
Catalog number	XC-CPU101-FC128K
Category	PLC CPU-module
Minimum order	1 Pcs
Document ID	EO-AAE3B68FA1
Generated	2026-08-06

Product Overview

Modular PLC, 24 V DC, 8DI, 6DO, RS232, optical CAN, 128kB

PLC XC101 Modular; Programmable with CODESYS V2; 8 ED; 6SD; RS232; CAN Optical; 64kB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > XC Modular PLC

Additional Product Information

EL-Nummer (Norway)4560925Modular PLC, 24 V DC, 8DI, 6DO, RS232, optical CAN, 128kBModular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. a particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.Delivery program

Digital input countDigital:8; of which usable as interrupt: 4Quantity of outputsTransistor: 6Built-in interfacesCANopen® (FO cable)

RS232DescriptionOptical CAN interface:Instructionsexpandable with ? expansions XI/OC

Only on connection with ?XI/OC rackUser memory128 KbyteCycle time for 1 k of instructions (Bit, Byte)< 0.5

msMemoryApplication/marker/retain data128 KB/8 KB/8 KBIntegrated Web servernoInformation about equipment

suppliedThe following accessory equipment is required: terminal clamps, module rack, batteryApprovalsEACTechnical data
GeneralStandardsIEC/EN 61131-2

EN 50178Ambient temperature0 - +55 °CStorage [?]-25 - +70 °CMounting positionHorizontalRelative humidity,
non-condensing (IEC/EN 60068-2-30)10 - 95 %Air pressure (operation)795 - 1080 hPaVibration resistance10...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XC-CPU101-FC128K-8DI-6DO with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.