

INDUSTRIAL COMPONENT DATA

+IZMX-M40-110AD 124296 EATON ELECTRIC Motor operator 110-125 VAC/DC

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-M40-110AD



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-M40-110AD
Catalog number	124296
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-41BDB334D6
Generated	2026-08-03

Product Overview

Motor operator 110-125 VAC/DC

The motor automatically tensions the spring force storage mechanism for remote or local actuation, with signaling switch zspring-operated stored-energy mechanism charged.z

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Motor operator 110-125 VAC/DC The motor automatically tensions the spring force storage mechanism for remote or local actuation, with signaling switch "spring-operated stored-energy mechanism charged." [Delivery program

Product range Accessories Accessories Remote switching Accessories Motor operator DC Maximum operating frequency [Actuations/minute] 3 Please note - the circuit-breaker's switching frequency = 60/h Rated control voltage [Us] 110 - 127 V AC 50/60 Hz

110 - 125 V DC V Operating range [x US] 0,85 - 1,1 Factor max. holding current [In] 3 AC / 2 DC A max. pick-up current (35ms) [In] 9 AC / 7.5 DC A max. continuous power [AC/DC] 425 AC / 275 DC VA/W max. pull-in power (35ms) [AC/DC] 3 VA/W For use with IZMX40...

INX40... Information about equipment supplied A signaling switch for the labeled "Spring-operated stored energy mechanism tensioned" message is included as standard. , Technical data

Necessary time required for charging the spring-operated stored energy mechanism at 1 x Us 3 s AC 50/60 Hz

3 s DC Rated operational current [In] 3 A AC 50/60 Hz

2 A DC A Starting current 6 A AC 50/60 Hz

8 A DC A Power consumption 450 VA AC 50/60 Hz

200 W DC , Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030) Electric engineering, automation, process control engineering / Low-voltage swi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-M40-110AD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.