

## INDUSTRIAL COMPONENT DATA

**+IZMX-M40-24DC 124290 EATON ELECTRIC 124290  
+IZMX-M40-24DC**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-M40-24DC



|                 |                                          |
|-----------------|------------------------------------------|
| Manufacturer    | EATON - MOELLER                          |
| MPN / Reference | +IZMX-M40-24DC                           |
| Catalog number  | 124290                                   |
| Category        | Motor operator for power circuit-breaker |
| Minimum order   | 1 Pcs                                    |
| Document ID     | EO-2326F8DC32                            |
| Generated       | 2026-08-04                               |

**Product Overview**

124290 +IZMX-M40-24DC

The motor automatically tensions the spring force storage mechanism for remote or local actuation, with signaling switch zspring-operated stored-energy mechanism charged.z

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

**Additional Product Information**

Motor operator 24 VDC The motor automatically tensions the spring force storage mechanism for remote or local actuation, with signaling switch "spring-operated stored-energy mechanism charged." [ Delivery program

Product range Accessories Accessories Remote switching Accessories Motor operator DC Maximum operating frequency [Actuations/minute] 3 Please note - the circuit-breaker's switching frequency = 60/h Rated control voltage [Us] 24 V DC V Operating range [x US] 0,85 - 1,1 Factor max. holding current [In] 7 A max. pick-up current (35ms) [In] 24.5 A max. continuous power [AC/DC] 200 VA/W max. pull-in power (35ms) [AC/DC] 3 VA/W For use with IZMX40...

INX40... Information about equipment supplied A signaling switch for the labeled "Spring-operated stored energy mechanism tensioned" message is included as standard. , Technical data

Necessary time required for charging the spring-operated stored energy mechanism at 1 x Us 3 s DC Rated operational current [In] 7 A DC A Starting current 14 A DC A Power consumption 200 W DC , Design verification as per IEC/EN 61439 Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0 Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030) Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Electrical drive for

circuit breakers ([email protected] [AKF010013]) Type of switch driv...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-M40-24DC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.