

INDUSTRIAL COMPONENT DATA

IZMX-M16-60DC 123994 EATON ELECTRIC Motor operator 60 VDC

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-M16-60DC



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-M16-60DC
Catalog number	123994
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-726F9508A7
Generated	2026-08-01

Product Overview

Motor operator 60 VDC

IZMX-M16-60DC

The motor automatically tensions the spring force storage mechanism for remote or local actuation, with signaling switch zspring-operated stored-energy mechanism charged.z

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Motor operator 60 VDCThe motor automatically tensions the spring force storage mechanism for remote or local actuation, with signaling switch "spring-operated stored-energy mechanism charged."Delivery program

Product rangeAccessoriesAccessoriesRemote switchingAccessoriesMotor operatorDCMaximum operating frequency [Actuations/minute]3Please note - the circuit-breaker's switching frequency = 60/hRated control voltage [Us]60 V DC VOperating range [x US]0,85 - 1,1 Factormax. holding current [In]3 Amax. pick-up current (35ms) [In]15 Amax. continuous power [AC/DC]150 VA/Wmax. pull-in power (35ms) [AC/DC]3 VA/WFor use withIZMX16... INX16...InstructionsAn additional control circuit terminal block is required for retrofitting.

For fixed mounting circuit-breakers?#156593 and withdrawable unit circuit-breakers ?#156590Information about equipment suppliedA signaling switch for the labeled "Spring-operated stored energy mechanism tensioned" message is included as standard.Technical data

Necessary time required for charging the spring-operated stored energy mechanism at 1 x Us s DCRated operational current [In]3 A DC AStarting current15 A DC APower consumption150 W DCDesign verification as per IEC/EN 61439

Operating ambient temperature min.-25 °C Operating ambient temperature max.+70 °C Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030) Electric engineering,
automation, process control engineering / Low-voltage switch techn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-M16-60DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.