

INDUSTRIAL COMPONENT DATA

Z-MS-2,5/2 248395 Y7-248395 EATON ELECTRIC Motor-Protective Circuit-Breakers, 1, 6-2, 5 A, 2 p

Brand: EATON - MOELLER | Manufacturer Part Number: Z-MS-2,5/2



Manufacturer	EATON - MOELLER
MPN / Reference	Z-MS-2,5/2
Catalog number	Y7-248395
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-45AE0BCBE0
Generated	2026-08-03

Product Overview

Motor-Protective Circuit-Breakers, 1, 6-2, 5 A, 2 p

Z-MS-2,5/2

Motor-protective circuit-breaker with thermal overload release and magnetic short-circuit release, for switching and protecting three-phase motors with outputs of up to 15 kW (380/400 V) or other loads with currents of up to 40 A, can also be used as a main switch, isolating characteristics to IEC/EN 60947, contact position display red/green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Motor-Protective Circuit-Breakers, 1,6-2,5A, 2pMotor-protective circuit-breaker with thermal overload release and magnetic short-circuit release, for switching and protecting three-phase motors with outputs of up to 15 kW (380/400 V) or other loads with currents of up to 40 A, can also be used as a main switch, isolating characteristics to IEC/EN 60947, contact position display red/green

General specificationsProduct nameEaton Distribution partsPart no.Z-MS-2,5/2EAN4015082483951Product

Length/Depth80 millimetreProduct height75 millimetreProduct width36 millimetreProduct weight0.244

kilogramCompliancesRoHS conformProduct TradenameNoneProduct TypeDistribution partsProduct Sub TypeNonePublic

ConsumptionYesProduct Family DescriptionES-PMCC-PDC-Eaton Distribution partsGlobally MarketableYesProduct

Specification DetailsActuator typeRocker leverAdjustment range short-term delayed short-circuit release - min25

AAdjustment range undelayed short-circuit release - max33 AAdjustment range undelayed short-circuit release - min25

ADegree of protectionIP20Device constructionComplete device in housingElectrical connection type of main circuitScrew

connectionEquipment heat dissipation, current-dependent3.7 W
Fitted with:Thermal protectionHeat dissipation per pole,
current-dependent1.85 W
Number of polesTwo-pole
Overload release current setting - max2.5 A
Overload release current setting - min1.6 A
Rated operating power at AC-3, 230 V0 kW
Rated operating power at AC-3, 400 V0.75 kW
Rated operating V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-MS-2,5/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.