

INDUSTRIAL COMPONENT DATA

PKE12 121721 Y7-121721 EATON ELECTRIC Motor-protective circuit-breaker, 3p, 12A, electronic, basic device

Brand: EATON - MOELLER | Manufacturer Part Number: PKE12



Manufacturer	EATON - MOELLER
MPN / Reference	PKE12
Catalog number	Y7-121721
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-A78B3A7F77
Generated	2026-08-04

Product Overview

Motor-protective circuit-breaker, 3p, 12A, electronic, basic device

PKE12

Eaton Moeller® series PKE12 Circuit-breaker, Basic device with standard knob, 12 A, Without overload releases, Screw terminals

Basic device motor-protective circuit-breaker, isolating function, can be expanded without tools with PKE-XTU... electronic control units for motor protection. Expandable with auxiliary contacts, voltage release, current limiter, door coupling handles. world-market device

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Motor-protective circuit-breaker Catalog Number 121721 Model Code PKE12
EAN 4015081195312 Product Length/Depth 101 mm Product Height 102.5 mm Product Width 45 mm Product Weight 0.33 kg
Compliances CE Marked Certifications UL 508

IEC 60947-4-1

EN 60947-4-1

CSA Std. C22.2 No. 14-10

VDE

CE

CSA Class No.: 3211-05

VDE 0660

CSA

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL File No.: E36332

IEC/EN 60947-4-1

UL

UL Category Control No.: NLRV

CSA File No.: 165628

IEC/EN 60947 Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Fitted with: Standard knob Functions Motor protection

Motor protection for heavy starting duty Number of poles Three-pole General

Degree of protection IP20

Terminals: IP00 Lifespan, electrical 50,000 operations (at 400V, AC-3) Lifespan, mechanical 50,000 Operations (Main conducting paths) Operating frequency 60 Operations/h Overload release current setting - min 0 A Overload release current setting - max 12 A Overvoltage category III Pollution degree 3 Product category Motor protective circuit breaker Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for Also motors with efficiency class IE3 Temperature compensation -5 - 40 °C to IEC/EN 60947, VDE 0660

-25 - 55 °C, Operating range Ambient conditions, mechan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.