

INDUSTRIAL COMPONENT DATA

PKE65/XTU-65 138516 Y7-138516 EATON ELECTRIC

Motor-protective circuit-breaker, 3p, +control option 8-65A

Brand: EATON - MOELLER | Manufacturer Part Number: PKE65/XTU-65



Manufacturer	EATON - MOELLER
MPN / Reference	PKE65/XTU-65
Catalog number	Y7-138516
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-D58BDA84BF
Generated	2026-08-06

Product Overview

Motor-protective circuit-breaker, 3p, +control option 8-65A

PKE65/XTU-65

Eaton Moeller® series PKE65 Motor-protective circuit-breaker, Complete device with standard knob, Electronic, 16 - 65 A, With overload release

Motor-protective circuit-breaker complete device (basic device and electronic control unit) according to IEC60947-4-1, electronic wide-range overload protection (4:1), phase-failure and unbalance protection, adjustable tripping class, high short-circuit breaking capacity. Expandable with auxiliary contact, voltage release, current limiter door coupling handles., ATEX accreditation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE System-protective circuit-breaker Catalog Number 138516 Model Code PKE65/XTU-65 EAN 4015081352951 Product Length/Depth 187 mm Product Height 162 mm Product Width 55 mm Product Weight 1.469 kg Certifications CE

CSA-C22.2 No. 60947-4-1-14

CSA

UL Category Control No.: NLRV

UL File No.: E36332

CSA File No.: 165628

UL

UL 60947-4-1

VDE 0660

IEC/EN 60947

CSA Class No.: 3211-05

IEC/EN 60947-4-1 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Fitted with: Standard knob Functions Motor protection for heavy starting duty

Overload release

Motor protection Number of poles Three-pole General

Current flow times - min For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

900 (Class 15) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cycle operation, Main conducting paths

500 (Class 5) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor). Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE65/XTU-65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.